

Certificate of Conformity

This is to Certify **DriStud Cool Window Flashing Tape**

Product Description

DriStud Cool Window Flashing Tape is a self-adhesive, pressure sensitive, polyethylene membrane material tape with a release backing. The tape is branded with the DriStud Cool Window Flashing Tape branding and CodeMark logo.

Complies with the Building Code of New Zealand:

When specified and installed in accordance with the requirements of this certificate, DriStud Cool Window Flashing Tape will comply with the following provisions of the NZ Building Code;

B1.3.1, B1.3.2, B1.3.3 (a, c, q), B1.3.4 (a, b, c, d, e)

B2.3.1 (b), B2.3.2 (a)

E2.3.2, E2.3.7 (a, b, c)

F2.3.1

Subject to the following conditions and limitations:

1. Must be installed in accordance with the DriStud Cool Window Flashing Tape Installation Manual Rev 1, July 2015. This is available at www.dristud.co.nz
2. The scope of this certificate covers the use of DriStud Cool Window Flashing Tape in buildings:
 - up to 10m in height, and
 - with a risk score less than 20, when evaluated against the E2/AS1 risk matrix, and
 - in wind zones up to extra high as defined in NZS 3604:2011, and
 - in all corrosion zones as defined in NZS3604:2011.
3. Installation at an ambient and substrate temperature of less than -6°C falls outside the scope of this certificate
4. The scope of the certificate covers the use of DriStud Cool Window Flashing Tape with DriStud Wall Wrap and rigid air barriers made from plywood, OSB or fibre cement
5. TCL Hunt Ltd will notifyASUREQuality in accordance with Regulation 15 of the Building (Product Certification) Regulations 2008

Date of Issue 15th July 2015

Certificate Number AQ-160715-CMNZ



John McKay, Chief Executive Officer, ASUREQuality Limited

CodeMark Certification Body

ASUREQuality, 11 Hull Road, Mt Maunganui
New Zealand
Tel. 0508 00 11 22
www.asurequality.com



CODEMARK™

Product Use and Scope

DriStud Cool Window Flashing Tape is intended for use in new and existing buildings in conjunction with an underlay or rigid air barrier. It is used around framed joinery openings and penetrations, providing a secondary weather resistant barrier. It is designed to be used in conjunction with air seals and joinery flashing systems, but not as a substitute. DriStud Cool Window Flashing Tape may also be used at joinery heads to seal flashing upstands to the building wrap. Where a rigid underlay has been installed, DriStud Cool Window Flashing Tape may be used to seal all junctions and penetrations.

It is suitable for use with timber and steel framed buildings as well as masonry structures. It may be used where the environmental temperature fluctuates between -25°C to 80°C.

Certificate Holder

TCL Hunt Ltd
7 Fisher Cres, Mt Wellington, Auckland 1064
PO Box 132-166, Sylvia Park, Auckland, 1644
www.dristud.co.nz
Ph +64 9 526 2700



www.jas-anz.org/register