

# Certificate of Conformity

This is to Certify **DriStud FRU 36 & DriStud FRU 38**

## Product Description

DriStud FRU 36 & DriStud FRU 38 are white synthetic tri-laminate roofing underlays that are water resistant, vapour permeable and fire retardant.

DriStud FRU 36 is a lighter grammage self-support roof underlay, whereas DriStud FRU 38 is heavier grammage self-support roof underlay.

## Complies with the Building Code of New Zealand:

If designed, installed and maintained in accordance with the conditions of this certificate, DriStud FRU 36 & DriStud FRU 38 roofing underlay will comply with;

B1 Structure - B1.3.1, B1.3.2, B1.3.3 (a), (h)

B2 Durability - B2.3.1 (a), B2.3.2 (b)

C3 Fire Affecting Areas beyond the Fire Source - C3.4 (c)

F2 Hazardous Building Material - F2.3.1

If designed, installed and maintained in accordance with the conditions of this certificate, DriStud FRU 36 & DriStud FRU 38 roofing underlay will contribute to compliance with;

E2 External Moisture - E2.3.1, E2.3.2, E2.3.7 (a), (b), (c)

## Subject to the following conditions and limitations:

1. Must be installed in accordance with the DriStud FRU 38 Installation Guide Rev 2.2 (August 2017) and DriStud FRU 36 Installation Guide Rev 3, (November 2017). These are available at [www.dristud.co.nz](http://www.dristud.co.nz).
2. DriStud FRU 36 & DriStud FRU 38 may be installed over timber and steel roof framing.
3. This certificate covers the use of DriStud FRU 36 & DriStud FRU 38 under: Masonry Tiles, Terracotta tiles, Metal tiles, Profiles metal claddings, slate and composite panels.
4. DriStud FRU 36 & FRU 38 can span up to 1200mm between adjacent supports. Where the span exceeds 1200mm or the roof pitch is  $\leq 10^\circ$  a corrosion resistant mesh or alternative i.e. plastic strapping must be used.
5. TCL Hunt Ltd will notify AsureQuality Ltd in accordance with Regulation 15 of the Building (Product Certification) Regulations 2008.



**CODEMARK™**

## Product Use and Scope

DriStud FRU 36 & DriStud FRU 38 are roofing underlays intended for use on new and existing buildings in wind zones up to and including 'Extra High', as defined in NZS 3604:2011.

DriStud FRU 36 & DriStud FRU 38 can be used where both heavy weight and/or self-support roof underlay is specified.

## Certificate Holder

TCL Hunt Ltd  
7 Fisher Cres, Mt Wellington, Auckland 1064  
PO Box 132-166, Sylvia Park, Auckland, 1644  
[www.dristud.co.nz](http://www.dristud.co.nz)  
Ph +64 9 526 2700



**JAS-ANZ**



[www.jas-anz.org/register](http://www.jas-anz.org/register)

**CodeMark Certification Body**

AsureQuality, 11 Hull Road,  
Mt Maunganui  
New Zealand  
Tel. 0508 00 11 22  
[www.asurequality.com](http://www.asurequality.com)

  
John McKay, Chief Executive Officer, AsureQuality Limited

**Date of Issue**

**10<sup>th</sup> September 2015**

**Certificate Number**

**AQ-100915-CMNZ  
(Rev 5 - Nov 17)**