

## DriStud Joining Tape

---

DriStud Joining Tape is a hand tearable joining tape, coated with a highly aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapour seal on all interior and exterior sheathing materials. DriStud Joining Tape exceeds most building code requirements and can be used for new construction as well as repair on all vapour barrier materials and vapour permeable wall and roof underlays. It is the highest performing, highest value product on the market and it is available in white at 48mm wide width.

### Product construction

Oriented Polyester and Acrylic Adhesive

### Features & Benefits

- High performance tape installs and performs well over a wide temperature range
- Excellent vapour barrier tape on polymer film
- Performs well as a joining tape on extruded foam products such as Styrofoam.
- Applies to most of the wall and roof underlays. We guarantee performance on all the DriStud wall and roof underlays and Tyvek.

### Technical Data

Properties	Test Method	DriStud Joining Tape
Product thickness	PSTC-133	0.087mm
Roll size		48mm x 50m
Peel Adhesion		
to stainless steel	PSTC-101	15.9N/25mm
to polyethylene	PSTC-101	5.6N/25mm
to Tyvek	PSTC-101	8.8N/25mm
Shear Adhesion	PSTC-107	>24 hrs @ 15.2 kPa
Tensile Strength	PSTC-131	90.4N/25mm
Elongation	PSTC-131	130%
WVTR	ASTM E96	0.061 perms
Service Temperature		-40 to 85 °C